

A Concurrent Language with a Uniform Treatment of Regions and Locks

Prodromos Gerakios Nikolaos Papaspyrou Konstantinos Sagonas

School of Electrical and Computer Engineering, National Technical University of Athens, Greece

{pgerakios,nickie,kostis}@softlab.ntua.gr

A challenge for programming language research is to design and implement multi-threaded low-level languages providing static guarantees for memory safety and freedom from data races. Towards this goal, we present a concurrent language employing safe region-based memory management and hierarchical locking of regions. Both regions and locks are treated uniformly, and the language supports ownership transfer, early deallocation of regions and early release of locks in a safe manner.

1 Introduction

Writing safe and robust code is a hard task; writing safe and robust multi-threaded low-level code is even harder. In this paper we present a minimal, low-level concurrent language with advanced region-based memory management and hierarchical lock-based synchronization primitives.

Region-based memory management achieves efficiency by bulk allocation and deallocation of objects in segments of memory called regions. Similar to other approaches, our regions are organized in a hierarchical manner such that each region is physically allocated within a single parent region and may contain multiple child regions. This hierarchical structure imposes an ownership relation as well as lifetime constraints over regions. Unlike other languages employing hierarchical regions, our language allows early subtree deallocation in the presence of region sharing between threads. In addition, each thread is obliged to release each region it owns by the end of its scope.

Multi-threaded programs that interact through shared memory generate random execution interleavings. A data race occurs in a multi-threaded program when there exists an interleaving such that some thread accesses a memory location while some other thread attempts to write to it. So far, type systems and analyses that guarantee race freedom [6] have mainly focused on lexically-scoped constructs. The key idea in those systems is to statically track or infer the lockset held at each program point. In the language presented in this paper, implicit reentrant locks are used to protect regions from data races. Our locking primitives are non-lexically scoped. Locks also follow the hierarchical structure of regions so that each region is protected by its own lock as well as the locks of all its ancestors.

Furthermore, our language allows regions and locks to be safely aliased, escape the lexical scope when passed to a new thread, or become logically separated from the remaining hierarchy. These features are invaluable for expressing numerous idioms of multi-threaded programming such as *sharing*, *region ownership* or *lock ownership transfers*, *thread-local regions* and *region migration*.

2 Language Design

We briefly outline the main design goals for our language, as well as some of the main design decisions that we made to serve these goals.

Low-level and concurrent. Our language must efficiently support systems programming. As such, it should cater for memory management and concurrency. It also needs to be low-level: it is not intended to be used by programmers but as a target language of higher-level systems programming languages.

Static safety guarantees. We define safety in terms of *memory safety* and absence of *data races*. A static type system should guarantee that well-typed programs are safe, with minimal run-time overhead.

Safe region-based memory management. Similarly to other languages for safe systems programming (e.g. Cyclone) our language employs region-based memory management, which achieves efficiency by *bulk allocation* and *deallocation* of objects in segments of memory (*regions*). Statically typed regions [13, 14] guarantee the absence of dangling pointer dereferences, multiple release operations of the same memory area, and memory leaks. Traditional stack-based regions [13] are limiting as they cannot be deallocated early. Furthermore, the stack-based discipline fails to model region lifetimes in concurrent languages, where the lifetime of a shared region depends on the lifetime of the longest-lived thread accessing that region. In contrast, we want regions that can be *deallocated early* and that can safely be *shared* between concurrent threads.

We opt for a *hierarchical region* [8] organization: each region is physically allocated within a single parent region and may contain multiple child regions. Early region deallocation in our multi-level hierarchy automatically deallocates the immediate subtree of a region without having to deallocate each region of the subtree recursively. The hierarchical region structure imposes the constraint that a child region is *live* only when its ancestors are live. In order to allow a function to access a region without having to pass all its ancestors explicitly, we allow ancestors to be abstracted (i.e., our language supports *hierarchy abstraction*) for the duration of the function call. To maintain the *liveness* invariant we require that the abstracted parents are *live* before and after the call. Regions whose parent information has been abstracted cannot be passed to a new thread as this may be unsound.

Race freedom. To prevent data races we use *lock-based* mutual exclusion. Instead of having a separate mechanism for locks, we opt for a uniform treatment of locks and regions: locks are placed in the same hierarchy as regions and enjoy similar properties. Each region is protected by its own private lock and by the locks of its ancestors. The semantics of region locking is that the entire subtree of a region is *atomically locked* once the lock for that region has been acquired. Hierarchical locking can model complex synchronization strategies and lifts the burden of having to deal with explicit acquisition of multiple locks. Although deadlocks are possible, they can be *avoided* by acquiring a single lock for a group of regions rather than acquiring multiple locks for each region separately. Additionally, our language provides explicit locking primitives, which in turn allow a higher degree of concurrency than lexically-scoped locking, as some locks can be released early.

Region polymorphism and aliasing. Our language supports *region polymorphism*: it is possible to pass regions as parameters to functions or concurrent threads. This enables *region aliasing*: one actual region could be passed in the place of two distinct formal region parameters. In the presence of mutual exclusion and early region deallocation, aliasing is dangerous. Our language allows safe region aliasing with minimal restrictions. The mechanism that we employ for this purpose also allows us to encode numerous useful idioms of concurrent programming, such as *region migration*, *lock ownership transfers*, *region sharing*, and *thread-local regions*.

3 Language Features through Examples

Our regions are lexically-scoped first-class citizens; they are manipulated via explicit handles. For instance, a region handle can be used for releasing a region early, for allocating references and regions within it, or for locking it. Our language uses a *type and effect system* to guarantee that regions and their contents are properly used. The details will be made clear in Sections 4 and 6. Here, we present the main features of our language through examples. We try to avoid technical issues as much as possible; however, some characteristics of the type and effect system are revealed in this section and their presence is justified. Furthermore, to simplify the presentation in this section, we use abbreviations for a few language constructs that we expect the readers will find more intuitive.

Example 1 (Simple Region Usage) This example shows a typical region use. New regions are allocated via the `newrgn` construct. This construct requires a handle to an existing region (*heap* in this case), in which the new region will be allocated, and introduces a type-level name (ρ) and a fresh handle (h) for the new region. The handle h is then used to allocate a new integer in region ρ ; a reference to this integer (z) is created. Finally, the region is deallocated before the end of its lexical scope.

```

newrgn  $\rho, h$  at heap in           //  $\{\rho^{1,1} \triangleright \rho_H\}$ 
  let  $z = \text{new } 10$  at  $h$  in
    ...
     $z := \text{deref } z + 5$ ;
    ...
    free  $h$ ;                       //  $\{\}$  — empty effect,  $\rho$  is no longer alive
  ...

```


The comments on the right-hand side of the example's code show the current *effect*. An effect is roughly a set of *capabilities* that are held at a given program point. Right after creation of region ρ , the entry $\rho^{1,1} \triangleright \rho_H$ is added to the effect; this means that a capability ("1,1" — we will later explain what this means) is held for region ρ , which resides in the heap region (ρ_H). Regions start their life as local to a thread and their contents can be directly accessed. For instance, a reference z can be created in ρ , dereferenced and assigned a new value, as long as the type system can verify that a proper capability for ρ is present in the current effect. Deallocation of ρ removes the capability from the effect; once that is done, the region's contents become inaccessible.

Example 2 (Hierarchical Regions) In the previous example a trivial hierarchy was created by allocating region ρ within the *heap* region. It is possible to construct richer region hierarchies. As in the previous example, the code below allocates a new region ρ_1 within the heap. Other regions can be then allocated within ρ_1 , e.g. ρ_2 ; this can be done by passing the handle of ρ_1 to the region creation construct. Similarly, regions ρ_3 and ρ_4 can be allocated within region ρ_2 .

```

newrgn  $\rho_1, h$  at heap in           //  $\{\rho_1^{1,1} \triangleright \rho_H\}$ 
  ...
  newrgn  $\rho_2, h_2$  at  $h_1$  in         //  $\{\rho_1^{1,1} \triangleright \rho_H, \rho_2^{1,1} \triangleright \rho_1\}$ 
    ...
    newrgn  $\rho_3, h_3$  at  $h_2$  in       //  $\{\rho_1^{1,1} \triangleright \rho_H, \rho_2^{1,1} \triangleright \rho_1, \rho_3^{1,1} \triangleright \rho_2\}$ 
      newrgn  $\rho_4, h_4$  at  $h_2$  in     //  $\{\rho_1^{1,1} \triangleright \rho_H, \rho_2^{1,1} \triangleright \rho_1, \rho_3^{1,1} \triangleright \rho_2, \rho_4^{1,1} \triangleright \rho_2\}$ 
    ...

```



Our language allows regions to be allocated at any level of the hierarchy. For instance, it is possible to allocate more regions within region ρ_1 , in the lexical scope of region ρ_4 .

Example 3 (Bulk Region Deallocation) In the first example a single region was deallocated. That region was a *leaf* node in the hierarchy; it contained no sub-regions. In the general case, when a region is deallocated, the entire subtree below that region is also deallocated. This is what happens if, in the code of the previous example, we deallocate region ρ_2 within the innermost scope; regions ρ_3 and ρ_4 are also deallocated. They are all removed from the current effect and thus are no longer accessible.

<pre> newrgn ρ_1, h at heap in // $\{\rho_1^{1,1} \triangleright \rho_H\}$... newrgn ρ_2, h_2 at h_1 in // $\{\rho_1^{1,1} \triangleright \rho_H, \rho_2^{1,1} \triangleright \rho_1\}$... newrgn ρ_3, h_3 at h_2 in // $\{\rho_1^{1,1} \triangleright \rho_H, \rho_2^{1,1} \triangleright \rho_1, \rho_3^{1,1} \triangleright \rho_2\}$ newrgn ρ_4, h_4 at h_2 in // $\{\rho_1^{1,1} \triangleright \rho_H, \rho_2^{1,1} \triangleright \rho_1, \rho_3^{1,1} \triangleright \rho_2, \rho_4^{1,1} \triangleright \rho_2\}$... free h_2; // $\{\rho_1^{1,1} \triangleright \rho_H\}$... // ρ_2, ρ_3 and ρ_4 are no longer alive </pre>	
---	--

Example 4 (Region Migration) A common multi-threaded programming idiom is to use *thread-local* data. At any time, only one thread will have access to such data and therefore no locking is required. A thread can transfer thread-local data to another thread but, doing so, it loses access to the data. This idiom is known as *migration*. Our language encodes thread-local data and data migration. As we have seen, newly created regions are considered thread-local; a capability for them is added to the current effect. We support data migration by allowing such capabilities to be transferred to other threads.

The following example illustrates region migration. A server thread is defined, which executes an infinite loop. In every iteration, a new region is created and is initialized with client data. The contents of the region are then processed and finally transferred to a newly created (spawned) thread.

```

def server =  $\Lambda \rho_H. \lambda \text{heap}.$ 
  while (true) do
    newrgn  $\rho, h$  at heap in           //  $\{\rho^{1,1} \triangleright \rho_H\}$ 
    let  $z = \text{wait\_data}[\rho](h)$  in     // region  $\rho$  is thread-local
    process( $z$ );
    spawn output $[\rho](h, z)$ ;          //  $\{\}$  — empty effect,  $\rho$  migrates to output
    ...                               //  $\rho$  cannot be accessed here

```

The server thread accepts the heap region and its handle. Within the infinite loop, it allocates a new region ρ in the heap. Its handle h is passed to function `wait_data`, which is supposed to fill the region ρ with client data (z). Function `process` is then called and works on the data. Until this point, region ρ is thread-local and accessible to the server thread, so no explicit locking is required. Now, let us assume that we want the processed data to be output by a different thread, e.g. to avoid an unnecessary delay on the server thread. A new thread `output` is spawned and receives the region handle h and the reference z to the client data. The capability $\rho^{1,1} \triangleright \rho_H$ is removed from the effect of `server` and is added to the input effect of thread `output`. Therefore, region ρ has now become thread-local to thread `output`, which can access it directly, while it is no longer accessible to the server thread.

Example 5 (Region Sharing) In the previous examples, capabilities for all regions were “1,1” which, as we roughly explained, corresponds to thread-local. In general, a capability for a region consists of two natural numbers; the first denotes the *region count*, whereas the second denotes the *lock count*. When the region count is positive, the region is definitely alive. Similarly, when the lock count is positive, memory


```

x := deref y;           // OK:  $\rho_1$  and  $\rho_2$  are locked
y := z                 // OK:  $\rho_2$  is locked

```

In order to instantiate ρ_1 and ρ_2 with the same region ρ , we can create two lock capabilities by using the lock operator twice on ρ 's handle h . Of course, the second use of lock will succeed immediately, as the region has already been locked by the same thread.

```

...                     //  $\{\rho^{2,0} \triangleright \rho_H\}$ 
lock h; lock h;         //  $\{\rho^{2,2} \triangleright \rho_H\}$ 
swap[ $\rho$ ][ $\rho$ ](a,b);      // each  $\rho$  parameter requires  $\rho^{1,1} \triangleright \rho_H$ 
unlock h; unlock h      //  $\{\rho^{2,0} \triangleright \rho_H\}$ 

```

Example 8 (Reentrant locks) Region aliasing introduces the need for reentrant locks. To see this, let us change the swapping function of the previous example, so that it receives two references in unlocked regions. For swapping their contents, it will have to acquire locks for the two regions (and release them, when they are no longer needed).

```

def swap =  $\Lambda \rho_1. \Lambda \rho_2. \lambda (h_1 : \text{rgn}(\rho_1), h_2 : \text{rgn}(\rho_2)).$ 
                $x : \text{ref}(\rho_1, \text{int}), y : \text{ref}(\rho_2, \text{int}))$  //  $\rho_1$  and  $\rho_2$  are unlocked

  lock h1;
  let z = deref x in      // OK:  $\rho_1$  is locked
    lock h2;
    x := deref y;         // OK:  $\rho_1$  and  $\rho_2$  are locked
    unlock h1;
    y := z;               // OK:  $\rho_2$  is locked
    unlock h2           // all locks can be released

```

Suppose again that we are to instantiate ρ_1 and ρ_2 with the same region ρ .

```

...                     //  $\{\rho^{2,0} \triangleright \rho_H\}$ 
swap[ $\rho$ ][ $\rho$ ](h,h,a,b); // each  $\rho$  parameter requires  $\rho^{1,0} \triangleright \rho_H$ 

```

We can easily see, however, that the run-time system cannot use binary locks; in that case, `swap[ $\rho$ ][ $\rho$ ]` would either come to a deadlock, waiting to obtain once more the lock that it has already acquired, or — worse — it might release the lock early (at `unlock h1`) and allow a data race to occur. To avoid unsoundness, we use *reentrant locks*: lock counts are important both for static typing and for the run-time system. A lock with a positive run-time count can immediately be acquired again, if it was held by the same thread. Moreover, a lock is released only when its run-time count becomes zero.

Example 9 (Pure and Impure Capabilities) Unrestricted region aliasing leads to unsoundness. Consider function `bad`, which accepts two integer references (x and y) in regions ρ_1 and ρ_2 , which are both locked. It lets ρ_1 migrate to a new thread and passes x as a parameter. It then assigns a value to y .

```

def bad =  $\Lambda \rho_1. \Lambda \rho_2. \lambda (x : \text{ref}(\rho_1, \text{int}), y : \text{ref}(\rho_2, \text{int})).$  //  $\rho_1$  and  $\rho_2$  must be both locked
  spawn f[ $\rho_1$ ](x);           //  $\rho_1$  migrates to f while locked
  y := 7                     // OK:  $\rho_2$  is still locked — WRONG!

```

A data race may occur if we call `bad` as follows; both threads have access to a , each holding a lock for ρ .

```

swap[ $\rho$ ][ $\rho$ ](a,a);           // each  $\rho$  parameter requires  $\rho^{1,1} \triangleright \rho_H$ 

```

Value	$v ::= f \mid c \mid \text{rgn}_l \mid \text{loc}_l$	Calling mode	$\xi ::= \text{seq} \mid \text{par}(\gamma)$
Function	$f ::= \lambda x. e \text{ as } \tau \xrightarrow{\gamma} \tau \mid \Lambda \rho. f$	Capability op	$\eta ::= \psi + \mid \psi -$
Expression	$e ::= x \mid c \mid f \mid (e e)^\xi \mid e[r] \mid \text{new } e \text{ at } e_2 \mid e := e \mid \text{loc}_l$ $\mid \text{deref } e \mid \text{newrgn } \rho, x \text{ at } e \text{ in } e \mid \text{cap}_\eta e \mid \text{rgn}_l$	Capability kind	$\psi ::= \text{rg} \mid \text{lk}$
Type	$\tau ::= b \mid \tau \xrightarrow{\gamma} \tau \mid \forall \rho. \tau \mid \text{ref}(\tau, r) \mid \text{rgn}(r)$	Capability	$\kappa ::= n, n \mid \bar{n}, \bar{n}$
Effect	$\gamma ::= \emptyset \mid \gamma, r^\kappa \triangleright \pi$	Region parent	$\pi ::= r \mid \perp \mid ?$
		Region	$r ::= \rho \mid \iota$

Figure 1: Syntax.

The cause of the unsoundness is that, in this last call to $\text{swap}[\rho][\rho]$, we allowed a single capability $\rho^{2,2} \triangleright \rho_H$ to be divided in two distinct capabilities $\rho^{1,1} \triangleright \rho_H$. More specifically, we divided the lock count in two and created two distinct lock capabilities, one of which escaped to a different thread through region migration. To resolve the unsoundness, we introduce the notion of *pure* (i.e., full) and *impure* (i.e., divided) capabilities. For instance, $\rho^{2,2} \triangleright \rho_H$ is a pure capability; when we divide it we obtain two impure halves, which we denote as $\rho^{1,1} \triangleright \rho_H$. Impure capabilities cannot be given to newly spawned threads when their lock count is positive. In contrast with pure capabilities, they represent inexact knowledge of a region's counts.

4 Language Description

The syntax of the language is illustrated in Figure 1. The language core comprises of variables (x), constants (c), functions, and function application. Functions can be region polymorphic ($\Lambda \rho. f$) and region application is explicit ($e[\rho]$). Monomorphic functions ($\lambda x. e$) must be annotated with their type. The application of monomorphic functions is annotated with a *calling mode* (ξ), which is seq for normal (sequential) application and $\text{par}(\gamma)$ for spawning a new thread.¹ Parallel application is annotated with the input effect of the new thread (γ); this annotation can be automatically inferred by the type checker. The constructs for manipulating references are standard. A newly allocated memory cell is returned by $\text{new } e_1 \text{ at } e_2$, where e_1 is the value that will be placed in the cell and e_2 is a handle of the region in which the new cell will be allocated. Standard assignment and dereference operators complete the picture.

The construct $\text{newrgn } \rho, x \text{ at } e_1 \text{ in } e_2$ allocates a new region ρ and binds x to the region *handle*. The new region resides in a *parent* region, whose handle is given in e_1 . The scope of ρ and x is e_2 , which must consume the new region by the end of its execution. A region can be consumed either by deallocation or by transferring its ownership to another thread. At any given program point, each region is associated with a *capability* (κ). Capabilities consist of two natural numbers, the *capability counts*: the *region* count and *lock* count, which denote whether a region is live and locked respectively. When first allocated, a region starts with capability $(1,1)$, meaning that it is live and locked, so that it can be exclusively accessed by the thread that allocated it. As we have seen, this is our equivalent of a thread-local region.

By using the construct $\text{cap}_\eta e$, a thread can *increment* or *decrement* the capability counts of the region whose handle is specified in e . The capability operator η can be, e.g., $\text{rg}+$ (meaning that the region count is to be incremented) or $\text{lk}-$ (meaning that the lock count is to be decremented).² When a region count reaches zero, the region may be physically deallocated and no subsequent operations can

¹In the examples of Section 3, we used more intuitive notation: we omitted seq and used the keyword spawn instead of par .

²The region manipulation operators used in Section 3 are simple abbreviations: $\text{share} \equiv \text{cap}_{\text{rg}+}$, $\text{unlock} \equiv \text{cap}_{\text{lk}-}$, etc.

Configuration	$C ::= S; T$	$E ::= \square \mid (E e)^{\xi} \mid (v E)^{\xi} \mid E[r]$
Threads	$T ::= \emptyset \mid T, n; e$	$\mid \text{newrgn } \rho, x \text{ at } E \text{ in } e \mid \text{cap}_{\eta} E$
Store	$S ::= \emptyset \mid S, \iota : (\theta, H, S)$	$\mid \text{new } E \text{ at } e\varepsilon \mid \text{new } v \text{ at } E\varepsilon$
Thread map	$\theta ::= \emptyset \mid \theta, n_1 \mapsto n_2, n_3$	$\mid \text{deref } E \mid E := e \mid v := E$
Memory heap	$H ::= \emptyset \mid H, \ell \mapsto v$	

Figure 2: Configurations, store, threads and evaluation contexts.

be performed on it. When a lock count reaches zero, the region is unlocked. As we explained, capability counts determine the validity of operations on regions and references. All memory-related operations require that the involved regions are live, i.e., the region count is greater than zero. Assignment and dereference can be performed only when the corresponding region is live and locked.

A capability of the form (n_1, n_2) is called a *pure* capability, whereas a capability of the form $(\overline{n_1}, \overline{n_2})$ is called an *impure* capability. In both cases, it is implied that the current thread can decrement the region count n_1 times and the lock count n_2 times. Impure capabilities are obtained by splitting pure or other impure capabilities into several pieces, e.g., $(3, 2) = (\overline{2}, \overline{1}) + (\overline{1}, \overline{1})$, in the same spirit as *fractional capabilities* [4]. As we explained in Example 9 of Section 3, these pieces are useful for region aliasing, when the same region is to be passed to a function in the place of two distinct region parameters. An impure capability implies that our knowledge of the region and lock count is inexact. The use of such capabilities must be restricted; e.g., an impure capability with a non-zero lock count cannot be passed to another thread, as it is unsound to allow two threads to simultaneously hold the same lock. Capability splitting takes place automatically with function application.

5 Operational Semantics

We define a *small-step* operational semantics for our language, using two evaluation relations, at the level of *threads* and *expressions* (Figures 3 and 4 on the next page). The thread evaluation relation transforms *configurations*. A configuration C (see Figure 2) consists of an abstract *store* S and a list of threads T .³ Each thread in T is of the form $n : e$, where n is a thread identifier and e is an expression. The store is a list of regions of the form $\iota : (\theta, H, S)$, where ι is a *region identifier*, θ is a thread map, H is a memory heap and S is the list of subregions in the region hierarchy. The thread map associates thread identifiers with capability counts for region ι , whereas the memory heap represents the region's contents, mapping locations to values.

A *thread evaluation context* E (Figure 2) is defined as an expression with a *hole*, represented as $\square$. The hole indicates the position where the next reduction step can take place. Our notion of evaluation context imposes a call-by-value evaluation strategy to our language. Subexpressions are evaluated in a left-to-right order.

We assume that concurrent reduction events can be totally ordered. At each step, a random thread (n) is chosen from the thread list for evaluation (Figure 3). It should be noted that the thread evaluation rules are the only *non-deterministic* rules in the operational semantics of our language; in the presence of more than one active threads, our semantics does not specify which one will be selected for evaluation. Threads that have completed their evaluation and have been reduced to *unit* values, represented as $()$, are removed from the active thread list (rule $E-T$). Rule $E-S$ reduces some thread n via the expression

³The order of elements in comma-separated lists, e.g. in a store S or in a list of threads T , is not important; we consider all list permutations as equivalent.

$$\begin{array}{c}
\frac{e' \equiv ((\lambda x. e \text{ as } \tau) v)^{\text{par}(\gamma_1)} \quad e'' \equiv ((\lambda x. e \text{ as } \tau) v)^{\text{seq}} \quad \text{fresh } n' \quad S' = \text{transfer}(S, n, n', \gamma_1)}{S; T, n: E[e'] \rightsquigarrow S'; T, n: E[()], n': e''} \quad (E\text{-SN}) \\
\\
\frac{S; e \rightarrow_n S'; e'}{S; T, n: E[e] \rightsquigarrow S'; T, n: E[e']} \quad (E\text{-S}) \quad \frac{}{S; T, n: () \rightsquigarrow S; T} \quad (E\text{-T})
\end{array}$$

Figure 3: Thread evaluation relation $C \rightsquigarrow C'$.

$$\begin{array}{c}
\frac{}{S; ((\lambda x. e \text{ as } \tau) v)^{\text{seq}} \rightarrow_n S; e[v/x]} \quad (E\text{-A}) \quad \frac{}{S; (\Lambda \rho. f)[r] \rightarrow_n S; f[r/\rho]} \quad (E\text{-RP}) \\
\\
\frac{(S', k) = \text{newrgn}(S, n, j)}{S; \text{newrgn } \rho, x \text{ at rgn}_j \text{ in } e \rightarrow_n S'; e[k/\rho][\text{rgn}_k/x]} \quad (E\text{-NG}) \quad \frac{S' = \text{updcap}(S, \eta, j, n)}{S; \text{cap}_\eta \text{ rgn}_j \rightarrow_n S'; ()} \quad (E\text{-C}) \\
\\
\frac{(S', \ell) = \text{alloc}(j, S, v)}{S; \text{new } v \text{ at rgn}_j \varepsilon \rightarrow_n S'; \text{loc}_\ell} \quad (E\text{-NR}) \quad \frac{S' = \text{update}(S, \ell, v, n)}{S; \text{loc}_\ell := v \rightarrow_n S'; ()} \quad (E\text{-AS}) \quad \frac{v = \text{lookup}(S, \ell, n)}{S; \text{deref loc}_\ell \rightarrow_n S; v} \quad (E\text{-D})
\end{array}$$

Figure 4: Expression evaluation relation $S; e \rightarrow_n S'; e'$.

evaluation relation. When a parallel function application redex is detected within the evaluation context of a thread, a new thread is created (rule $E\text{-SN}$). The redex is replaced with a unit value in the currently executed thread and a new thread is added to the thread list, with a *fresh* thread identifier. The *partial* function $\text{transfer}(S, n, n', \gamma_1)$ updates the thread maps of all regions specified in γ_1 , transferring capabilities between threads n and n' . It is undefined when this transfer is not possible.

The expression evaluation relation is defined in Figure 4. The rules for reducing function application ($E\text{-A}$) and region application ($E\text{-RP}$) are standard. The remaining rules make use of five *partial* functions that manipulate the store. These functions are undefined when their constraints are not met. All of them require that some region is *live*. A region is *live* when the sum of all region counts in the thread map associated with that region is positive and all ancestors of the region are *live* as well. In addition to liveness, some of these functions require that some region is *accessible* to the currently executed thread. Region r is accessible to some thread n (and *inaccessible* to all other threads) when r is live and the thread map associated with r , or with some ancestor of r , maps n to a positive lock count.

- $\text{alloc}(j, S, v)$ is used in rule $E\text{-NR}$ for creating a new reference. It allocates a new object in S . The object is placed in region j and is set to value v . Region j must be live. Upon success, the function returns a pair (S', ℓ) containing the new store and a fresh location for the new object.
- $\text{lookup}(S, \ell, n)$ is used in rule $E\text{-D}$ to look up the value of location ℓ in S . The region in which ℓ resides must be accessible to the currently executed thread n . Upon success, the function returns the value v stored at ℓ .
- $\text{update}(S, \ell, v, n)$ is used in rule $E\text{-AS}$ to assign the value v to location ℓ in S . The region in which ℓ resides must be accessible to the currently executed thread n . Upon success, the function returns the new store S' .
- $\text{newrgn}(S, n, j)$ is used in rule $E\text{-NG}$ to create a new region in S . The new region is allocated within j , which must be live. Its thread map is set to $n \mapsto 1, 1$. Upon success, the function returns a pair (S', k) containing the new store and a fresh region name for the new region.
- $\text{updcap}(S, \eta, j, n)$ is used in rule $E\text{-C}$. This operation updates S by modifying the region or lock count of thread n for region j . Upon success, the function returns the new store S' . When a lock

$$\begin{array}{c}
\frac{R; \Delta \vdash \tau \quad \tau \equiv \tau_1 \xrightarrow{\gamma_1 \rightarrow \gamma_2} \tau_2 \quad R; M; \Delta; \Gamma, x : \tau_1 \vdash e : \tau_2 \& (\gamma_1; \gamma_2)}{R; M; \Delta; \Gamma \vdash \lambda x. e \text{ as } \tau : \tau \& (\gamma; \gamma)} \quad (T-F) \quad \frac{R; M; \Delta; \Gamma \vdash e_1 : \tau_1 \xrightarrow{\gamma_1 \rightarrow \gamma_2} \tau_2 \& (\gamma; \gamma') \quad \xi \neq \text{seq} \Rightarrow \tau_2 = \langle \rangle \quad R; M; \Delta; \Gamma \vdash e_2 : \tau_1 \& (\gamma'; \gamma'') \quad \xi \vdash \gamma'' = \gamma_2 \oplus (\gamma' \ominus \gamma_1)}{R; M; \Delta; \Gamma \vdash (e_1 e_2)^\xi : \tau_2 \& (\gamma; \gamma'')} \quad (T-AP) \\
\\
\frac{R; M; \Delta; \Gamma \vdash e : \text{ref}(\tau, r) \& (\gamma; \gamma') \quad \text{is_accessible}(\gamma', r)}{R; M; \Delta; \Gamma \vdash \text{deref } e : \tau \& (\gamma; \gamma')} \quad (T-D) \quad \frac{R; M; \Delta; \Gamma \vdash e_1 : \text{rgn}(r) \& (\gamma; \gamma') \quad r \in \text{dom}(\gamma') \quad R; \Delta \vdash \tau \quad R; M; \Delta, \rho; \Gamma, x : \text{rgn}(\rho) \vdash e_2 : \tau \& (\gamma', \rho^{1,1} \triangleright r; \gamma'') \quad \rho \notin \text{dom}(\gamma'')}{R; M; \Delta; \Gamma \vdash \text{newrgn } \rho, x \text{ at } e_1 \text{ in } e_2 : \tau \& (\gamma; \gamma'')} \quad (T-NG) \\
\\
\frac{R; M; \Delta; \Gamma \vdash e_1 : \tau \& (\gamma; \gamma') \quad R; M; \Delta; \Gamma \vdash e_2 : \text{rgn}(r) \& (\gamma'; \gamma'') \quad r \in \text{dom}(\gamma'')}{R; M; \Delta; \Gamma \vdash \text{new } e_1 \text{ at } e_2 \varepsilon : \text{ref}(\tau, \rho) \& (\gamma; \gamma'')} \quad (T-NR) \quad \frac{R; M; \Delta; \Gamma \vdash e_1 : \text{rgn}(r) \& (\gamma; \gamma', r^{\kappa} \triangleright \pi) \quad \kappa' = \llbracket \eta \rrbracket(\kappa) \quad \gamma'' = \text{live}(\gamma', r^{\kappa'} \triangleright \pi)}{R; M; \Delta; \Gamma \vdash \text{cap}_\eta e_1 : \langle \rangle \& (\gamma; \gamma'')} \quad (T-CP)
\end{array}$$

Figure 5: Selected typing rules.

update is requested and the lock is held by another thread, the result is undefined. In this case, rule *E-C* cannot be applied and the operation will block, until the lock is available.

The operational semantics may get stuck when a *deadlock* occurs. Our semantics will also get stuck when a thread attempts to access a memory location without having acquired an appropriate lock for this location. In this case, $\text{update}(S, \ell, v, n)$ and $\text{lookup}(S, \ell, n)$ are undefined and it is impossible to perform a single step via rules *E-AS* or *E-D*. The same is true in several other situations (e.g. when referring to a non-existent region or location). Threads that may cause a data race will definitely get stuck.

We follow a different approach from related work, e.g. the work of Grossman [10], where a special kind of value *junk_v* is often used as an intermediate step when assigning a value *v* to a location, before the real assignment takes place, and type safety guarantees that no junk values are ever used. As described above, we use a more direct approach by incorporating the locking mechanism in the operational semantics. Our progress lemma in Section 7 guarantees that, at any time, *all* threads can make progress and, therefore, a possible implementation does not need to check liveness or accessibility at run-time.

6 Static Semantics

In this section we discuss the most interesting parts of our type system. As we sketched in Section 3, to enforce our safety invariants, we use a *type and effect system*. Effects are used to statically track region capabilities. An effect (γ) is a list of elements of the form $r^{\kappa} \triangleright \pi$, denoting that region *r* is associated with capability κ and has parent π , which can be another region, $\perp$, or $?$. Regions whose parents are $\perp$ or $?$ are considered as roots in our region hierarchy. We assume that there is an initial (physical) root region corresponding to the entire heap, whose handle is available to the main program. The parent of the heap region is $\perp$. More (logical) root regions can be created using hierarchy abstraction. The abstract parent of a region that is passed to a function is denoted by $?$.

The syntax of types in Figure 1 (on page 85) is more or less standard. A collection of base types *b* is assumed; the syntax of values belonging to these types and operations upon such values are omitted from this paper. We assume the existence of a *unit* base type, which we denote by $\langle \rangle$. Region handle types $\text{rgn}(r)$ and reference types $\text{ref}(\tau, r)$ are associated with a type-level region *r*. Monomorphic function types carry an *input* and an *output effect*. A well-typed expression *e* has a type τ under an input effect γ and results in an output effect γ' . The typing relation (see Figure 5) is denoted by $R; M; \Delta; \Gamma \vdash e : \tau \& (\gamma; \gamma')$ and uses four typing contexts: a set of region literals (*R*), a mapping of locations to types (*M*), a set of region variables (Δ), and a mapping of term variables to types (Γ). The effects that appear in our typing

$$\begin{array}{c}
\frac{\xi \vdash \gamma = \gamma_1 \oplus \gamma_r \quad \xi \vdash \gamma' = \gamma_2 \oplus \gamma_r \quad \gamma' = \text{live}(\gamma') \quad \text{consistent}(\gamma; \gamma'')}{\xi \vdash \text{seq} \Rightarrow \text{abs_par}(\gamma; \gamma_1) \subseteq \text{dom}(\gamma'') \quad \xi \vdash \text{par}(\gamma'') \Rightarrow \gamma_1 = \gamma''' \wedge \gamma_2 = \emptyset} \text{ (ESJ)} \\
\xi \vdash \gamma'' = \gamma_2 \oplus (\gamma \ominus \gamma_1) \\
\\
\frac{}{\xi \vdash \gamma = \emptyset \oplus \gamma} \text{ (ES-N)} \quad \frac{\pi' \in \{\pi, ?\} \quad \xi \vdash \text{par}(\gamma') \Rightarrow \pi' \neq ? \quad \xi \vdash \kappa = \kappa_1 + \kappa_2 \quad \xi \vdash \gamma = \gamma_1 \oplus \gamma_2}{\xi \vdash \gamma, r^{\kappa} \triangleright \pi = \gamma_1, r^{\kappa_1} \triangleright \pi' \oplus \gamma_2, r^{\kappa_2} \triangleright \pi} \text{ (ES-C)} \\
\\
\frac{\text{rg}(\kappa) = \text{rg}(\kappa_1) + \text{rg}(\kappa_2) \quad \text{lk}(\kappa) = \text{lk}(\kappa_1) + \text{lk}(\kappa_2) \quad \text{rg}(\kappa_1) > 0 \quad \text{is_pure}(\kappa_1) \Leftrightarrow \text{is_pure}(\kappa_2) \quad \text{is_pure}(\kappa_1) \Rightarrow \kappa = \kappa_1 \quad \xi \neq \text{seq} \wedge \neg \text{is_pure}(\kappa_1) \Rightarrow \text{lk}(\kappa_2) = 0}{\xi \vdash \kappa = \kappa_1 + \kappa_2} \text{ (CS)}
\end{array}$$

Figure 6: Effect and capability splitting.

$$\begin{array}{c}
\frac{(r^{\kappa} \triangleright \pi) \in \gamma \quad \text{rg}(\kappa) > 0 \quad \pi \in \{\perp, ?\}}{\text{is_live}(\gamma, r)} \quad \frac{(r^{\kappa} \triangleright r') \in \gamma \quad \text{rg}(\kappa) > 0 \quad \text{is_live}(\gamma, r')}{\text{is_live}(\gamma, r)} \\
\\
\frac{(r^{\kappa} \triangleright \pi) \in \gamma \quad \text{lk}(\kappa) > 0}{\text{is_accessible}(\gamma, r)} \quad \frac{(r^{\kappa} \triangleright r') \in \gamma \quad \text{is_accessible}(\gamma, r')}{\text{is_accessible}(\gamma, r)}
\end{array}$$

Figure 7: Auxiliary predicates: region liveness and accessibility.

$$\begin{array}{ll}
\text{rg}(\kappa) & = n_1 \quad \text{if } \kappa = n_1, n_2 \vee \kappa = \overline{n_1, n_2} \\
\text{lk}(\kappa) & = n_2 \quad \text{if } \kappa = n_1, n_2 \vee \kappa = \overline{n_1, n_2} \\
\text{dom}(\gamma) & = \{r \mid (r^{\kappa} \triangleright \pi) \in \gamma\} \\
\text{live}(\gamma) & = \{r^{\kappa} \triangleright \pi \mid (r^{\kappa} \triangleright \pi) \in \gamma \wedge \text{is_live}(\gamma, r)\} \\
\text{is_pure}(\kappa) & = \exists n_1. \exists n_2. \kappa = n_1, n_2 \\
\text{consistent}(\gamma_1; \gamma_2) & = (\forall (r^{\kappa} \triangleright \pi) \in \gamma_1. \forall (r^{\kappa'} \triangleright \pi') \in \gamma_2. \pi = \pi' \wedge (\text{is_pure}(\kappa) \Leftrightarrow \text{is_pure}(\kappa'))) \\
& \quad \wedge \text{dom}(\gamma_2) \subseteq \text{dom}(\gamma_1) \wedge \text{live}(\gamma_1) = \gamma_1 \wedge \text{live}(\gamma_2) = \gamma_2 \\
\text{abs_par}(\gamma_1; \gamma_2) & = \left\{ r \mid (r^{\kappa} \triangleright r') \in \gamma_1 \wedge (r^{\kappa'} \triangleright ?) \in \gamma_2 \right\}
\end{array}$$

Figure 8: Auxiliary functions and predicates.

relation must satisfy a *liveness invariant*: all regions that appear in the effect are *live*, i.e., their region counts and those of all their ancestors are positive. Thus, in order to check if a region r is live in the effect γ , we only need to check that $r \in \text{dom}(\gamma)$.

The typing rule for lambda abstraction (*T-F*) requires that the body e is well-typed with respect to the effects ascribed on its type. The typing rule for function application (*T-AP*) splits the output effect of e_2 (γ'') by subtracting the function's input effect (γ_1). It then joins the remaining effect with the function's output effect (γ_2). In the case of parallel application, rule *T-AP* also requires that the return type is unit. The splitting and joining of effects is controlled by the judgement $\xi \vdash \gamma'' = \gamma_2 \oplus (\gamma \ominus \gamma_1)$, which is defined in Figure 6 (the auxiliary functions and predicates are defined in Figures 7 and 8). It enforces the following properties:

- the liveness invariant for γ'' ;
- the consistency of γ and γ'' , i.e., regions cannot change parent and capabilities cannot switch from pure to impure or vice versa; the domain of γ'' is a subset of the domain of γ ;
- for sequential application, all parent regions that become abstracted for the duration of the function call must be live after the function returns;
- for parallel application, the thread output effect must be empty, the thread input effect must not contain impure capabilities with positive lock counts and hierarchy abstraction is disallowed.

The typing rules for references are standard. In Figure 5 we only show the rules for dereference

(*T-D*) and reference allocation (*T-NR*). The former checks that region r is *accessible*. The latter only checks that the region r is *live*. The rule for creating new regions (*T-NG*) checks that e_1 is a handle for some live region r' . Expression e_2 is type checked in an extended typing context (i.e., ρ and $x : \text{rgn}(\rho)$ are appended to Δ and Γ respectively) and an extended input effect (i.e., a new effect is appended to the input effect such that the new region is live and accessible to this thread). The rule also checks that the type and the output effect of e_2 do not contain any occurrence of region variable ρ . This implies that ρ must be *consumed* by the end of the scope of e_2 . The capability manipulation rule (*T-CP*) checks that e is a handle of a live region r . It then modifies the capability count of r as dictated by function $\llbracket \eta \rrbracket$, which increases or decreases the region or the lock count of its argument, according to the value of η . The dynamic semantics ensures that an operational step is performed when the actual counts are consistent with the desired output effect. For instance, if the lock of region r is held by some other executing thread, the evaluation of cap_{lk+} must be suspended until the lock can be obtained. On the other hand, the evaluation of cap_{rg-} does not need to suspend but may not be able to physically deallocate a region, as it may be used by other threads.

7 Type Safety

In this section we discuss the fundamental theorems that prove type safety of our language.⁴ The type safety formulation is based on proving the *preservation* and *progress* lemmata. Informally, a program written in our language is safe when for each thread of execution an evaluation step can be performed or that thread is waiting for a lock (*blocked*). As discussed in Section 5, a thread may become stuck when it accesses a region that is not live or accessible (these are obviously the interesting cases in our concurrent setting; of course a thread may become stuck when it performs a non well-typed operation). Deadlocked threads are not considered to be stuck.

Definition 1 (Thread Typing) Let T be a collection of threads. Let $R;M;\delta$ be a global typing context, in which δ is a mapping from thread identifiers to effects, used only for metatheoretic purposes. For each thread $n:e$ in T , we take $\delta(n)$ to be the input effect that corresponds to the evaluation of expression e . The following rules define *well-typed* threads.

$$\frac{}{R;M;\emptyset \vdash_T \emptyset} \quad \frac{R;M;\delta \vdash_T T \quad R;M;\emptyset;\emptyset \vdash e : \langle \rangle \& (\gamma;\emptyset) \quad n \notin \text{dom}(\delta)}{R;M;\delta, n \mapsto \gamma \vdash_T T, n:e}$$

Definition 2 (Store Consistency) A store S is *consistent* with respect to an effect mapping δ when the following conditions are met:

- *Region consistency*: the set of region names occurring in the co-domain of δ is a subset of the set of region names in S .
- *Static-dynamic count consistency*: for each region, the dynamic region and lock counts of some thread must be greater than or equal to the corresponding static counts of the same thread.
- *Mutual exclusion*: only one thread may have a positive lock count in δ for a particular region j . Additionally, only this thread is allowed to access or lock sub-regions of j .

Definition 3 (Store Typing) A store S is *well-typed* with respect to $R;M;\delta$ (we denote this by $R;M;\delta \vdash_{str} S$) when the following conditions are met:

⁴Full proofs and a full formalization of our language are given in the companion technical report [9].

- S is *consistent* with respect to δ ,
- the set of region names in S is equal to R ,
- the set of locations in M is equal to the set of locations in S , and
- for each location ℓ , the stored value $S(\ell)$ is closed and has type $M(\ell)$ with empty effects, i.e., $R; M; \emptyset; \emptyset \vdash S(\ell) : M(\ell) \& (\emptyset; \emptyset)$.

Definition 4 (Configuration Typing) A configuration $S; T$ is *well-typed* with respect to $R; M; \delta$ (we denote this by $R; M; \delta \vdash_C S; T$) when the collection of threads T is well-typed with respect to $R; M; \delta$ and the store S is well-typed with respect to $R; M; \delta$.

Definition 5 (Not stuck) A configuration $S; T$ is *not stuck* when each thread in T can take one of the evaluation steps in Figure 3 (E -S, E -T or E -SN) or it is waiting for a lock held by some other thread.

Given these definitions, we can now present the main results of this paper. The *progress* and *preservation* lemmata are first formalized at the *program* level, i.e., for all concurrently executed threads.

Lemma 1 (Progress — Program) Let $S; T$ be a closed well-typed configuration with $R; M; \delta \vdash_C S; T$. Then $S; T$ is not stuck.

Lemma 2 (Preservation — Program) Let $S; T$ be a well-typed configuration with $R; M; \delta \vdash_C S; T$. If the operational semantics takes a step $S; T \rightsquigarrow S'; T'$, then there exist $R' \supseteq R$, $M' \supseteq M$ and δ' such that the resulting configuration is well-typed with $R'; M'; \delta' \vdash_C S'; T'$.

An expression-level version for each of these two lemmata is required, in order to prove the above. At the *expression* level, progress and preservation are defined as follows.

Lemma 3 (Progress — Expression) Let S be a well-typed store with $R; M; \delta, n \mapsto \gamma \vdash_{str} S$ and let e be a closed well-typed *redex* with $R; M; \emptyset; \emptyset \vdash e : \tau \& (\gamma; \gamma')$. Then exactly one of the following is true:

- e is of the form $\text{cap}_{|k|+} \text{rgn}_j$ and j is a live but inaccessible region to thread n , or
- e is of the form $(\lambda x. e_1 \text{ as } \tau v)^{\text{par}(\gamma)}$ or
- there exist S' and e' such that $S; e \rightarrow_n S'; e'$.

Lemma 4 (Preservation — Expression) Let e be a well-typed expression with $R; M; \emptyset; \emptyset \vdash e : \tau \& (\gamma; \gamma')$ and let S be a well-typed store with $R; M; \delta, n \mapsto \gamma \vdash_{str} S$. If the operational semantics takes a step $S; e \rightarrow_n S'; e'$, then there exist $R' \supseteq R$, $M' \supseteq M$ and γ' such that the resulting expression and the resulting store are well-typed with $R'; M'; \emptyset; \emptyset \vdash e' : \tau \& (\gamma'; \gamma'')$ and $R'; M'; \delta[n \mapsto \gamma'] \vdash_{str} S'$.

The *type safety* theorem is a direct consequence of Lemmata 1 and 2. Let function `main` be the initial program, let ι_H be global heap region and let the initial typing contexts R_0 and δ_0 and the initial program configuration $S_0; T_0$ be defined by the following singleton lists: $R_0 = \{\iota_H\}$, $\delta_0 = \{1 \mapsto \iota_H^{1,0} \triangleright \perp\}$, $\theta_0 = \{1 \mapsto 1, 0\}$, $S_0 = \{\iota_H : (\theta_0, \emptyset, \emptyset)\}$, and $T_0 = \{1 : (\text{main}[\iota_H] \text{rgn}_{\iota_H})^{\text{seq}}\}$.

Theorem 1 (Type Safety) If the initial configuration $S_0; T_0$ is well-typed with $R_0; \emptyset; \delta_0 \vdash_C S_0; T_0$ and the operational semantics takes any number of steps $S_0; T_0 \rightsquigarrow^n S_n; T_n$, then the resulting configuration $S_n; T_n$ is not stuck.

The empty (except for R_0 that contains only ι_H) contexts that are used when typechecking the initial configuration $S_0; T_0$ guarantee that all functions in the program are closed and that no explicit region values (rgn_ℓ) or location values (loc_ℓ) are used in the source of the original program.

8 Related Work

The first statically checked stack-based region system was developed by Tofte and Talpin [13]. Since then, several memory-safe systems that enabled early region deallocation for a sequential language were proposed [1, 12, 15, 7]. Cyclone [11] and RC [8] were the first imperative languages to allow safe region-based management with explicit constructs. Both allowed early region deallocation and RC also introduced the notion of multi-level region hierarchies. RC programs may throw region-related exceptions, whereas our approach is purely static. Both Cyclone and RC make no claims of memory safety or race freedom for concurrent programs. Grossman proposed a type system for safe multi-threading in Cyclone [10]. Race freedom is guaranteed by statically tracking locksets within lexically-scoped synchronization constructs. Grossman’s proposal allows for fine-grained locking, but only deals with stack-based regions and does not enable early release of regions and locks. In contrast, we support hierarchical locking, as opposed to just primitive locking, and bulk region deallocation.

Statically checked region systems have also been proposed [3, 17, 16] for real-time Java to rule out dynamic checks imposed by the language specification. Boyapati et al. [3] introduce hierarchical regions in ownership types but the approach suffers from the same disadvantages as Grossman’s work. Additionally, their type system only allows sub-regions for *shared* regions, whereas we do not have this limitation. Boyapati also proposed an ownership-based type system that prevents deadlocks and data races [2]; in contrast to his system, we support locking of arbitrary nodes in the region hierarchy. Static region hierarchies (depth-wise) have been used by Zhao [17]. Their main advantage is that programs require fewer annotations compared to programs with explicit region constructs. In the same track, Zhao et al. [16] proposed implicit ownership annotations for regions. Thus, classes that have no explicit owner can be allocated in any static region. This is a form of *existential ownership*. In contrast, we allow a region to completely abstract its owner/ancestor information by using the *hierarchy abstraction* mechanism. None of the above approaches allow full ownership abstraction for region subtrees.

Cunningham et al. [5] proposed a universe type system to guarantee race freedom in a calculus of objects. Similarly to our system, object hierarchies can be atomically locked at any level. Unlike our system, they do not support early lock releases and lock ownership transfers between threads. Consequently, their system cannot encode two important aspects of multi-threaded programming: thread-locality and data migration. Finally, our system provides explicit memory management and supports separate compilation.

The main limitation of our work is that we require explicit annotations regarding ownership and region capabilities. Moreover, our locking system offers coarser-grained locking than most other related works. The use of hierarchical locking avoids some, though not all, deadlocks.

9 Concluding Remarks

In this paper, we have presented a concurrent language employing region-based memory management and locking primitives. Regions and locks are organized in a common hierarchy and treated uniformly. Our language allows atomic deallocation and locking of entire subtrees at any level of the hierarchy; it also allows region and lock capabilities to be transferred between threads, encoding useful idioms of concurrent programming such as *thread-local data* and *data migration*. The type system guarantees the absence of memory access violations and data races in the presence of region aliasing.

We are currently integrating our system in Cyclone. In the future, we are planning to extend our type system to achieve an exact correspondence between static and dynamic capability counts, and provide deadlock freedom guarantees.

References

- [1] Alexander Aiken, Manuel Fähndrich & Raph Levien (1995): *Better Static Memory Management: Improving Region-Based Analysis of Higher-Order Languages*. In: *Proc. of the ACM SIGPLAN Conference on Programming Language Design and Implementation*. pp. 174–185.
- [2] Chandrasekhar Boyapati, Robert Lee & Martin Rinard (2002): *Ownership Types for Safe Programming: Preventing Data Races and Deadlocks*. In: *Proc. of the ACM SIGPLAN Conference on Object-Oriented Programming, Systems, Languages, and Applications*. pp. 211–230.
- [3] Chandrasekhar Boyapati, Alexandru Salcianu, William S. Beebe & Martin Rinard (2003): *Ownership Types for Safe Region-based Memory Management in Real-Time Java*. In: *Proc. of the ACM SIGPLAN Conference on Programming Language Design and Implementation*. pp. 324–337.
- [4] John Boyland (2003): *Checking Interference with Fractional Permissions*. In: *Proc. of the 10th International Symposium on Static Analysis, LNCS 2694*. Springer, pp. 55–72.
- [5] David Cunningham, Sophia Drossopoulou & Susan Eisenbach (2007): *Universe Types for Race Safety*. In: *Proc. of the 1st International Workshop on Verification and Analysis of Multi-threaded Java-like Programs*. pp. 20–51.
- [6] Cormac Flanagan & Martín Abadi (1999): *Object Types Against Races*. In: *Proc. of the 10th International Conference on Concurrency Theory, LNCS 1664*. Springer, pp. 288–303.
- [7] Matthew Fluet, Gregory Morrisett & Amal Ahmed (2006): *Linear Regions Are All You Need*. In: *Proc. of the European Symposium on Programming, LNCS 3924*. Springer, pp. 7–21.
- [8] David Gay & Alexander Aiken (2001): *Language Support for Regions*. In: *Proc. of the ACM SIGPLAN Conference on Programming Language Design and Implementation*. pp. 70–80.
- [9] Prodromos Gerakios, Nikolaos Papaspyrou & Konstantinos Sagonas (2009): *A Concurrent Language With a Uniform Treatment of Regions and Locks*. Technical Report CSD-SW-TR-7-09, Software Engineering Laboratory, National Technical University of Athens. Available at http://www.softlab.ntua.gr/~pgerakios/papers/reglock_techrep09.pdf.
- [10] Dan Grossman (2003): *Type-safe Multithreading in Cyclone*. In: *Proc. of the ACM SIGPLAN International Workshop on Types in Languages Design and Implementation*. pp. 13–25.
- [11] Dan Grossman, Gregory Morrisett, Trevor Jim, Michael Hicks, Yanling Wang & James Cheney (2002): *Region-based Memory Management in Cyclone*. In: *Proc. of the ACM SIGPLAN Conference on Programming Language Design and Implementation*. pp. 282–293.
- [12] Fritz Henglein, Henning Makholm & Henning Niss (2001): *A direct approach to control-flow sensitive region-based memory management*. In: *Proc. of the 3rd ACM SIGPLAN International Conference on Principles and Practice of Declarative Programming*. pp. 175–186.
- [13] Mads Tofte & Jean-Pierre Talpin (1994): *Implementation of the Typed Call-by-value λ -calculus using a Stack of Regions*. In: *Proc. of the ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*. pp. 188–201.
- [14] David Walker, Karl Crary & Gregory Morrisett (2000): *Typed Memory Management via Static Capabilities*. *ACM Transactions on Programming Languages and Systems* 22(4), pp. 701–771.
- [15] David Walker & Kevin Watkins (2001): *On Regions and Linear Types*. In: *Proc. of the ACM SIGPLAN International Conference on Functional Programming*. pp. 181–192.
- [16] Tian Zhao, Jason Baker, James Hunt, James Noble & Jan Vitek (2008): *Implicit ownership types for memory management*. *Science of Computer Programming* 71(3), pp. 213–241.
- [17] Tian Zhao, James Noble & Jan Vitek (2004): *Scoped Types for Real-Time Java*. In: *Proc. of the 25th IEEE International Real-Time Systems Symposium*. pp. 241–251.